

# TUTELA CAR ZC 75 SYNTH

## DESCRIPTION

Fully synthetic lubricating oil for mechanical transmissions of cars.  
For use in gear/differential units, including those with hypoid torque, whenever lubrication with Extreme Pressure (E.P.) characteristics is required.

## CHARACTERISTICS

Special E.P./anti-wear additives in order to guarantee optimal protection of the transmission components even in extreme conditions (starting, acceleration etc.) and with high load at low revs.

Specific viscosity grade in order to optimise gear handling at every operating temperature.

Excellent fluency during cold running to ensure excellent shift ability even at the severest temperatures.

Optimal adhesiveness of the lubricant in order to ensure optimal protection of the mechanical parts in all conditions of lubrication, and prevents excessive mechanical noise.

Fuel economy product reduces frictions in and consequently reduces fuel consumption.

Fully synthetic formulation to ensure excellent thermal-oxidative resistance, therefore prolonging the period between oil changes.

TUTELA ZC 75 SYNTH exceeds the quality requirements of the major European Manufacturers and therefore can be used in cars of every make, type and power rating.



## ADVICE ON USE

TUTELA ZC 75 SYNTH has a grade of SAE 75W-80 for all year use.  
Changes should be made in accordance with the Manufacturers recommendations.

## RECOMMENDED BY

Fiat, Lancia, Alfa Romeo.

## TECHNICAL DATA

SAE 75W-80, API GL 5, MIL-L-2105 D